

The OVALIS fireplace stove and its large combustion chamber will allow you to enjoy an entertaining view of the flames.

OVALIS Fireplace stoves

The compact shape of the OVALIS fireplace stove combined with the wide combustion chamber make it a perfect fit for your interior.

This fireplace stove is suitable for low-energy homes. The designer stainless steel ventilated handle permits use when the stove is lit. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood.

OVALIS 05


ceramic



Prices on request at your seller

order code: **OVALIS 05**

Glaze colours



Technical parameters

Height	1071 mm
Width	630 mm
Depth	398 mm
Door height	678 mm
Door width	534 mm
Door depth	114 mm
Weight	143 kg
Regulated output	3,0-7,8 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	938 mm
Draught	11 Pa
Efficiency	83,5 %
Average wood consumption	1,6 kg/h
A+	

Download

[Declaration about qualities](#)
[EC declaration of conformity](#)
[Ecodesign \(EU 2015/1185\)](#)
[Energy label and product sheet](#)
[Energy label \(EU 2015/1186\)](#)
[General instructions](#)
[Installation instructions](#)
[Technical documentation](#)
[Technical sheet](#)
[Warranty sheet](#)
[Download our catalogue!](#)