

SPIRIT Tiled accumulation fireplaces with lifting door

Appealing fireplace with three-side glazing, sophisticated details and focus on overall design and technical workmanship: These elements feature an impressive complex, addressing even the most demanding customers. The structure of the fireplace is covered with large format ceramic tiles that are ideal for efficient heat transmission.

Tiled accumulation fireplaces SPIRIT C1 are also suitable for low energy houses. They have sliding doors with precise and easy operation SILENT LIFT. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. In order to optimise the combustion process, tertiary air is led to the upper section of the combustion chamber. Innovative exhaust gas management system DOUBLE SPIN increases overall efficiency of the unit. Standard flue gas outlet is on the top or in the back. Secondary air intake will provide for door glass cleaning to avoid dirt deposits, a person sitting at the stove can look into the fire, without being disturbed by dirty glass of the door. Primary and secondary air intake is easily controlled by a one control element. Sufficient air for an optimum combustion process will be provided by the EAI system (external air intake from the exterior). The fireplace can be improved by installation of accumulation fittings, intended for accumulation of heat and its subsequent transfer back into the room, continuing even during several hours after the flame has extinguished. Thanks to back side shielding, the stove can be installed close to the wall. SPIRIT C2 M model is fitted with removable metal cornice.

SPIRIT C2

tile



Prices on request at your seller

order code: SPI C2



Glaze colours



125 mm

Technical parameters

Height 1703 mm
Width 834 mm
Depth 532 mm
Weight 318 kg
Regulated output 3,9-10,1 kW
Smoke flue diameter 150 mm
Flue socket diameter 150 mm

Axis height of rear outlet 1320/1370 mm

Draught 12 Pa
Efficiency 82,8 %
Average wood consumption 2,2 kg/h

Accessories

Α+

External air intake diameter

Accumulation set for design fireplaces (AKKUM CARA 01) CARA C GLASS PLINTH

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!