

# **DYNAMIC fireplace inserts** FOR LONG-LASTING ACCUMULATION HEATING WITH DOUBLE **GLAZING**

DYNAMIC fireplace inserts are the ideal choice for installations using accumulation elements. When assembled, these radiant accumulation stoves are the result of cooperation between the stove builder and the user. The output, size of the combustion chamber and the amount of accumulation are scaled to the specific building and the customer's requirements. Thanks to the ability to store and radiate heat, accumulation stoves are among the best and healthiest means of heating. Fire-place inserts should be purchased with MAMMOTH accumulation rings or the accumulation modular system, which represents the ultimate in heat storage.

DYNAMIC fireplace inserts have a design print on the double glazed door (suitable for low-energy houses when installed with accumulation casing). They have an external air intake (EAI) system, and are designed for closed, built-in accumulation. The combustion chamber is lined with 5 cm thick chamotte bricks and thanks to the secondary air intake, the glass on the door is constantly "washed" to prevent the build-up of deposits. The primary and secondary (tertiary) air intake can be regulated by a single control element. DYNAMIC fireplace inserts are not supplied with smoke extraction components (spigot). The customer must buy these separately as accessories according to the intended use. The fireplace insert cannot be connected directly to the chimney.

### **DYNAMIC B3G 38.50.01**



Prices on request at your seller

order code: DB3F 01

with back stoking

optional shifting of hinges for both doors











# **Technical parameters**

Height 957 mm
Width 606 mm
Depth 577 mm
Door height 455 mm
Door width 339 mm
Weight 171 kg
Regulated output 5,0-13,0 kW

Regulated output 5,0-13,0 kW

Smoke flue diameter 180 / 200 mm

Flue socket diameter 180 / 200 mm

External air intake diameter 150 mm

Draught 12 Pa

Efficiency 85,4 %

Average wood consumption 2,8 kg/h

Α+

### **Accessories**

ACCUMULATION SET of ROMOTOP MAMMOTH RINGS - 8 pcs (AKKUM KV 08B)

ADJUSTABLE LEGS - 190 mm

AIRBOX 01 IMPRESSION

**CAST IRON FLANGE 200** 

CAST IRON TURNING DOME WITH ELBOW 180

DESIGN HANDLE for the rear door (left opening)

DESIGN HANDLE for the rear door (right opening)

FRAME D3F RAM 04 cover deep

FRAME D3F RAM 06 cover standard

HOT AIR EXCHANGER for DYNAMIC 3G fireplace inserts

MAMMOTH accumulation ring

RECESSED HANDLE

REMOVABLE HANDLE

TECHNICAL FRAME DB3F RAM01 4S

# **Download**

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!