

HEAT fireplace inserts WITH SIDE OPENING AND SPLIT CORNER GLAZING

HEAT corner fireplace inserts with side opening are a compelling and modern addition to any interior. Let their pleasant warmth captivate you - making any home cozier, adding a touch of timeless design and a unique atmosphere.

HEAT fireplace inserts are intended for convection as well as accumulation operation with the use of ventilation grates. Corner glazing (left, right) is made of two parts. The door frame is made of a special rigid rolled profile. The glass in the doors includes a design print. An EAI (external air intake) system is included. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. A MAMMOTH side accumulation set and upper accumulation rings can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert.

HEAT R/L 2G S 65.51.40.21



Prices on request at your seller

Split glazing - right variant - order code: **HR2SG 21**

Split glazing - left variant - order code: **HL2SG 21**

without grate set (optional)

maximum of 2 side accumulation sets

Technical parameters

Height	1146 mm
Width	714,5 mm
Depth	468,5 mm
Door height	470 mm
Door width	652 mm
Door depth	397 mm
Weight	162 kg
Regulated output	3,5-9,0 kW
Smoke flue diameter	180-250 mm
Flue socket diameter	200 mm
External air intake diameter	150 mm
Draught	12 Pa
Efficiency	84,8 %
Average wood consumption	1,9 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

FRAME HR2SG RAM04 cover, deep, universal

FRAME HR2SG RAM06 4S universal, shallow

GRATE SET (H3 ROST 01)

REMOVABLE HANDLE

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!