

IMPRESSION fireplace inserts WITH LIFTING DOOR AND DOUBLE STRAIGHT GLAZING

If you are looking for both beauty and functionality, then the IMPRESSION fireplace insert with lifting door is the right choice for you. Decorate your home with a solitaire feature whose design will be the highlight of every room.

IMPRESSION fireplace inserts have unusually high glass windows, offering a luxurious view of the fire. Double glazing in the specially rigid profile of the door frame allows these fireplace inserts to be used for accumulation and convection operation. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The lifting door is operated using a removable handle, which can optionally be replaced by a fixed handle. The combustion chamber is available in black or cream colour with an optional change for the furnace grate. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. Fireplace inserts are equipped with a EAI (external air intake), which can be easily connected using the AIRBOX rotating elbow. The flue gas exhaust can be connected from the side or the top. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

IMPRESSION 2g L 80.60.01



Prices on request at your seller

order code: **I2LH 01**

maximum of 4 side accumulation sets

the combustion chamber is optional (crema or black) and needs be ordered separately!

Technical parameters

| | |
|------------------------------|-------------|
| Height | 1538 mm |
| Width | 1135 mm |
| Depth | 529 mm |
| Door height | 559 mm |
| Door width | 785 mm |
| Weight* | 220 kg |
| Regulated output | 5,5-14,3 kW |
| Smoke flue diameter | 160-200 mm |
| Flue socket diameter | 200 mm |
| External air intake diameter | 150 mm |
| Axis height of rear outlet | 1190 mm |
| Draught | 12 Pa |
| Efficiency | 80,2 % |
| Average wood consumption | 3,1 kg/h |

*weight including black / cream combustion chamber

A

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 01 IMPRESSION

COMBUSTION CHAMBER I2LH TOP01 black

COMBUSTION CHAMBER I2LH TOP02 cream

CONTRA-WEIGHT IMPRESSION

CONVECTION COVER for IMPRESSION 2g L 67.60.01, 2g L 80.60.01, 2g L 93.60.01 fireplace insert

FRAME I2LH RAM11 cover standard

FRAME I2LH RAM12 cover standard

FRAME I2LH RAM13 standard

FRAME I2LH RAM14 standard

FRAME I2LH RAM15 support

GRATE SET (H3 ROST 01)

HANDLING SET

IMPRESSION FIXED HANDLE

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts (AKKUM KV 06)

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)