

The ALEA fireplace stove includes a rotating design that allows you to enjoy viewing the flames from multiple angles.

ALEA A Fireplace stoves

The ALEA A fireplace stove will always adapt to your needs. Its rotating combustion chamber ensures you will always have a great view of the beautiful dancing flames, and the accumulation system above the combustion chamber will let you make great use of the heat released during combustion.

This fireplace stove is suitable for low-energy homes. An EAI (External Air Intake) system is included. The ventilated designer handle permits use when the stove is lit. The door can be locked in the open position. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. Additionally, you can purchase extra accumulation elements that radiate heat for up to 4 hours. The rotating combustion chamber allows you to view your fire from multiple angles.

ALEA 04 A

sandstone



Prices on request at your seller

order code: ALEA 04 A



Technical parameters

Height 1584 mm Width 468 mm 468 mm Depth Weight 177 kg Regulated output 2,9-7,4 kW Smoke flue diameter 150 mm Flue socket diameter 150 mm External air intake diameter 125 mm

Axis height of rear outlet 1129.5/1376.5 mm

Draught 12 Pa
Efficiency 82,9 %
Average wood consumption 1,6 kg/h

Α+

Accessories

Accumulation set for fireplace stoves (AKKUM 02)

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!