

## STROMBOLI N Fireplace stoves

**The large combustion chamber on its elegant pedestal and rotating mechanism of the STROMBOLI N fireplace stove offer you the opportunity to enjoy its radiating heat anywhere in the room.**

This fireplace stove is the perfect fit for modern interiors in particular. An EAI (External Air Intake) system is included. The standard version includes an upper flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The rotating combustion chamber allows you to view the flames from multiple angles.

### STROMBOLI N 04

sandstone



Prices on request at your seller  
order code: **STROMBOLI N04**

## Technical parameters

Height	1073 mm
Width	666 mm
Depth	475 mm
Weight	229 kg
Regulated output	4,5-11,7 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Draught	12 Pa
Efficiency	79,4 %
Average wood consumption	2,8 kg/h

A

## Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)