

BELO 3S A Fireplace stoves

The uniqueness of the BELO 3S A fireplace stove is guaranteed by its elegant door and side glazing, allowing the heat to radiate to three sides and adding a whole new dimension to watching your fire. Accumulation tiles can be placed above the combustion chamber, prolonging heat radiation by several hours.

This fireplace stove is suitable for low-energy homes. The fully glazed door is decorated with designer prints. The triple-sided glazing allows you to view the fire from multiple angles. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for a small amount of wood or tools. Additionally, you can purchase extra accumulation elements that radiate heat long after the stove has gone out.

BELO 3S 01 A

steel



order code: **BELO 3S 01 A**



Technical parameters

Height	1571 mm
Width	533 mm
Depth	406 mm
Door height	880 mm
Door width	447 mm
Door depth	129 mm
Weight	176 kg
Regulated output	2,5-6,4 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1073/1406 mm
Draught	12 Pa
Efficiency	80,5 %
Average wood consumption	1,4 kg/h
A+	

Accessories

Accumulation set for fireplace stoves (AKKUM 01)

Download

[Declaration about qualities](#)

[Energy label and product sheet](#)

[General instructions](#)

[More about accumulation in Romotop fireplace stoves](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)