

BELORADO A Fireplace stoves

The tall, unique BELORADO A fireplace stove dominates any space. The precisely created details in combination with a sophisticated structure meet all modern architectural requirements.

This fireplace stove is suitable for low-energy homes. The fully glazed door is decorated with designer prints. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for a small amount of wood or tools. Additionally, you can purchase extra accumulation elements that radiate heat for up to 5.5 hours.

BELORADO 04 A

sandstone



order code: **BELORADO 04 A**



Technical parameters

Height	1571 mm
Width	533 mm
Depth	406 mm
Door height	880 mm
Door width	447 mm
Door depth	129 mm
Weight	212 kg
Regulated output	2,5-6,4 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1073/1407 mm
Draught	12 Pa
Efficiency	80,5 %
Average wood consumption	1,4 kg/h
A+	

Accessories

Accumulation set for fireplace stoves (AKKUM 01)

Download

[Declaration about qualities](#)

[Energy label and product sheet](#)

[General instructions](#)

[More about accumulation in Romotop fireplace stoves](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)