

## ESQUINA N Fireplace stoves

**This slim, angled model with a tall glazed door will catch the attention of every visitor. The exceptional corner glass door provides more intense contact with the flames from all parts of the room.**

The ESQUINA N fireplace stove is suitable for low-energy homes. An EAI (External Air Intake) system is included. The ventilated designer handle permits use when the stove is lit. The door can be locked in the open position. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the accumulation of soot. The combustion chamber is lined with white MATRIX chamotte brick. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for storing a small amount of wood or tools. Additionally, you can purchase extra accumulation elements that radiate heat for up to 5 hours.

### ESQUINA N

steel



Prices on request at your seller

order code: **ESQUINA N**



## Technical parameters

Height	1506 mm
Width	403 mm
Depth	403 mm
Weight	179 kg
Regulated output	3,0-7,7 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1383 mm
Draught	12 Pa
Efficiency	81,4 %
Average wood consumption	1,7 kg/h
A+	

## Accessories

Accumulation set for fireplace stoves (AKKUM 03)

BOX low narrow

BOX low wide

BOX tall

## Download

Declaration about qualities

Energy label and product sheet

General instructions

Technical documentation

Technical sheet

Warranty certificate

Download our catalogue!