

EVORA A Fireplace stoves

A slender, tall stove with a popular oval base and high heat radiation capacity.

The EVORA A fireplace stove is suitable for low-energy homes. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for storing a small amount of wood or tools. Additionally, you can purchase extra accumulation elements that radiate heat for up to 5.5 hours.

EVORA 03 A

steel



Prices on request at your seller
order code: **EVORA 03 AKUM**



Technical parameters

Height	1312 mm
Width	528 mm
Depth	398 mm
Weight	133 kg
Regulated output	2,0-6,5 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	863/1133 mm
Draught	12 Pa
Efficiency	80,5 %
Average wood consumption	1,2 kg/h
A+	

Accessories

Accumulation set for fireplace stoves (AKKUM 01)

Download

[Declaration about qualities](#)

[Energy label and product sheet](#)

[General instructions](#)

[More about accumulation in Romotop fireplace stoves](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)