

MALAGA N Tiled stoves

The MALAGA N 03 tiled accumulation stove and Malaga N 01 tiled stove are the perfect fit for both modern and rustic interiors. The foundation of the Malaga N 03 tiled stove is a fireplace insert, to which you can also connect an accumulation exchanger.

Tiled fireplace stoves are suitable for low-energy houses. EAI (external air intake) system is included. The standard version gives the option of connecting an upper or rear flue gas exhaust. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. The combustion chamber is lined with chamotte brick tiles. Primary and secondary air intake is regulated by a single control element. An accumulation exchanger that radiates heat for up to 8.5 hours can be purchased separately for the stove.

MALAGA N 03

ceramic



Prices on request at your seller
order code: **MALAGA N03**



Glaze colours



Technical parameters

Height	1554 mm
Width	600 mm
Depth	470 mm
Weight	234 kg
Regulated output	2,0-6,0 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	100 mm
Axis height of rear outlet	920/1362 mm
Draught	12 Pa
Efficiency	80,3 %
Average wood consumption	1,1 kg/h
A+	

Accessories

Accumulating exchanger 07 AKU-001 - KV075

Download

- Assembly procedure
- Declaration about qualities
- Energy label and product sheet
- Instruction manual
- Technical documentation
- Technical sheet
- Warranty certificate
- Download our catalogue!