

OVALIS A Fireplace stoves

A sensitive fusion of all the major dimensions of the OVALIS A fireplace stove has resulted in a unique design. The rounded and unique dimensions of the glass provide a large area for direct observation of your fire. Accumulation tiles can be placed above the combustion chamber, prolonging heat radiation by several hours.

This fireplace stove is suitable for low-energy homes. The designer stainless steel ventilated handle permits use when the stove is lit. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood. Additionally, you can purchase extra accumulation elements that radiate heat for up to 5.5 hours.

OVALIS 02 A

serpentine



Prices on request at your seller

order code: **OVALIS 02 A**



Technical parameters

| | |
|------------------------------|-------------|
| Height | 1390 mm |
| Width | 628 mm |
| Depth | 398 mm |
| Door height | 678 mm |
| Door width | 534 mm |
| Door depth | 114 mm |
| Weight | 175 kg |
| Regulated output | 3,0-7,8 kW |
| Smoke flue diameter | 150 mm |
| Flue socket diameter | 150 mm |
| External air intake diameter | 125 mm |
| Axis height of rear outlet | 938/1183 mm |
| Draught | 11 Pa |
| Efficiency | 83,5 % |
| Average wood consumption | 1,6 kg/h |
| A+ | |

Accessories

Accumulation set for fireplace stoves (AKKUM 01)

Download

[Declaration about qualities](#)

[Energy label and product sheet](#)

[General instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)