

PALEA Fireplace stoves

The beauty of PALEA fireplace stoves is perfectly emphasized by their large glass door, offering a unique view of the fire. Lose yourself in the dancing flames. This fireplace stove can be fitted with special accumulation tiles in the space above the combustion chamber. This “mass” of accumulation elements can extend the heat radiation period of the stove by several hours.

This fireplace stove is suitable for low-energy homes. Radius glass intensifies the look on flames from different angles. Thanks to the secondary air intake, the door glass is air-washed to prevent the accumulation of soot. The primary and secondary air intakes are regulated by a single control element. The standard version includes the option to connect an upper or rear flue gas exhaust. The combustion chamber is lined with chamotte brick tiles. An EAI (External Air Intake) system is included. Additionally, you can purchase extra accumulation elements that radiate heat for up to 5.5 hours.

PALEA 02

serpentine



Prices on request at your seller

order code: **PALEA 02**



Technical parameters

Height	1335 mm
Width	520 mm
Depth	425 mm
Weight	196 kg
Regulated output	2,0-6,5 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	880/1150 mm
Draught	12 Pa
Efficiency	80,5 %
Average wood consumption	1,2 kg/h
A+	

Accessories

Accumulation set for fireplace stoves (AKKUM 01)

Download

[Declaration about qualities](#)

[Energy label and product sheet](#)

[General instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)