

## ALEDO Fireplace stoves

**ALEDO fireplace stoves are characterized by an elegant design, sophisticated external air intake and a fully glazed door that provides an uninterrupted view of the flames.**

This fireplace stove is suitable for low-energy homes. The stove door includes a large glazed area with a designer print. The stove includes an EAI (External Air Intake) system. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood.

### **ALEDO 01**

ceramic



Prices on request at your seller

order code: **ALEDO 01**



## Glaze colours



## Technical parameters

Height	862 mm
Width	740 mm
Depth	321 mm
Door height	589 mm
Door width	644 mm
Weight	151 kg
Regulated output	3,0-7,8 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	729 mm
Draught	11 Pa
Efficiency	83,5 %
Average wood consumption	1,6 kg/h
A+	

## Accessories

EAI COVER for ALEDO

## Download

- Declaration about qualities
- Energy label and product sheet
- Instruction manual
- Technical documentation
- Technical sheet
- Warranty certificate
- Download our catalogue!