

The modern design and state-of-the-art wood combustion technology are guaranteed to satisfy even the most demanding customers. A sensitive combination of a large designer door glazing print with varnished control elements has given birth to the unique design of OVALIS G fireplace stoves.

OVALIS G Fireplace stoves

The rounded and unique dimensions of the OVALIS G stove glass provide a large area for direct observation of your fire.

This fireplace stove is suitable for low-energy homes. The fully glazed door is decorated with designer prints. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for a small amount of wood or tools.

OVALIS G 05

ceramic



Prices on request at your seller
order code: **OVALIS G 05**



Glaze colours



Technical parameters

Height	1071 mm
Width	630 mm
Depth	398 mm
Door height	676 mm
Door width	534 mm
Door depth	115 mm
Weight	141 kg
Regulated output	3,0-7,8 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	938 mm
Draught	11 Pa
Efficiency	83,5 %
Average wood consumption	1,6 kg/h
A+	

Download

- [Declaration about qualities](#)
- [Energy label and product sheet](#)
- [Instruction manual](#)
- [Technical documentation](#)
- [Technical sheet](#)
- [Warranty certificate](#)
- [Download our catalogue!](#)