

CARA C N 03 Design fireplace with lifting door

The CARA C N 03 design fireplace stove responds to trends and needs of the modern interior architecture. Sensitively balanced exterior proportions, clean lines, large varnished metal sheeting and dominating large three-sided glazing create an imposing unit addressing the most demanding customers.

The precise and light movement of the door, made possible through the SILENT LIFT system, complements it all. The rear shielding allows you to place the fireplace right next to a wall. An EAI (External Air Intake) system is included. The innovative DOUBLE SPIN flue gas system increases the stove's efficiency. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the accumulation of soot. The combustion chamber is lined with chamotte bricks. It does not include a grate as standard, but this can be added on demand. The stove is connected to a tertiary air intake. The primary and secondary air intakes are regulated by a single control element. Additionally, you can purchase extra accumulation elements that radiate heat long after the fireplace has gone out.

CARA C N 03

steel



Prices on request at your seller

Split glazing - order code: **CARA C N 03**



Technical parameters

Height	1641 mm
Width	924 mm
Depth	577 mm
Door height	420 mm
Door width	670 mm
Door depth	272 mm
Weight	295 kg
Regulated output	3,9-10,1 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1346 mm
Draught	11 Pa
Efficiency	82,9 %
Average wood consumption	2,2 kg/h
A+	

Accessories

Accumulation set for CARA C, CARA R/L fireplace stove
AIRBOX 01
GRATE SET for Romotop CARA design fireplace stove
HANDLING SET

Download

Declaration about qualities
Energy label and product sheet
General instructions
Technical documentation
Technical sheet
Warranty certificate
Download our catalogue!