

## CARA CS 02 Design fireplace with lifting door

**The magic of fire in perfect balance with aesthetics and technology. The CARA CS 02 is a leaner variant which will perfectly suit low-energy homes.**

Indeed, this high quality fireplace is especially suitable for low-energy homes. The precise and light movement of the door, made possible through the SILENT LIFT system, complements it all. The rear shielding allows you to place the fireplace right next to a wall. An EAI (External Air Intake) system is included. The innovative DOUBLE SPIN flue gas system increases the stove's efficiency. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the accumulation of soot. The combustion chamber is lined with chamotte bricks. It does not include a grate as standard, but this can be added on demand. The stove is connected to a tertiary air intake. The primary and secondary air intakes are regulated by a single control element. Additionally, you can purchase extra accumulation elements that radiate heat long after the fireplace has gone out. The fireplace prominently features natural stone.

### CARA CS 02

serpentine



Prices on request at your seller

Split glazing - order code: **CARA CS 02**



## Technical parameters

Height	1648 mm
Width	774 mm
Depth	577 mm
Door height	420 mm
Door width	520 mm
Door depth	271 mm
Weight	303 kg
Regulated output	2,9-7,4 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1346 mm
Draught	10 Pa
Efficiency	82,1 %
Average wood consumption	1,6 kg/h
A+	

## Accessories

Accumulation set for CARA CS fireplace stove

GRATE SET for Romotop CARA design fireplace stove

## Download

[Declaration about qualities](#)

[General instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)