



ANGLE R/L 2g L 66.44.44.01

We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

- IMPRESSION R/L 2g L 71.60.34.21 - corner fireplace insert with lifting door and split glazing
- IMPRESSION R/L 2g L 83.60.34.21 - corner fireplace insert with lifting door and split glazing

Combustion aesthetics

- completely reworked combustion air distribution
- **DOUBLE SPIN flue gas system**

New system for door suspension at the center of gravity

- minimization of mechanical stress on door frame and running gear

ROMOTOP convection flaps

- **dissipation of excessive heat from the space above door**
- significantly longer service life of running gear
- keeping the convection tightness
- **flaps are shut even in case of slight door opening**

Heavy duty professional ball running gear

- precision door guide, correctly fitted door, tightness of combustion chamber
- distribution of mechanical stress to numerous roller elements, long service life
- location of running gear on the outside of the fireplace insert

Torsionally reinforced door frame

- **prevents frame deformation leading to possible cracks in glass**

Innovative glass attachment

- **away from edges capable of initiating cracks**

Combustion quality

- precise door guide in ball running gear
- DOUBLE SPIN flue gas system
- door with smooth close finish
- extra combustion air

Comfort

- more ergonomic door opening
- ROMOTOP convection flaps
- new 200 mm spigot ensures both, standard direct installing with pipes and direct installing of ROMOTOP MAMMOTH rings right on the insert

Bent glazing - right variant - order code: **AR2LE 01**

Bent glazing - left variant - order code: **AL2LE 01**

Technical parameters

Height	1430 mm
Width	743 mm
Depth	605 mm
Door height	407 mm
Door width	620 mm
Door depth	400 mm
Weight	252 kg
Regulated output	3,5-9,0 kW
Smoke flue diameter	180-250 mm
Flue socket diameter	200 mm
External air intake diameter	150 mm
Draught	12 Pa
Efficiency	84,8 %
Average wood consumption	1,9 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 190 mm

CAST IRON TURNING DOME 180

CAST IRON TURNING DOME 200

HANDLING SET

MAMMOTH accumulation ring

ROMOTOP CONVECTION EXCHANGER

ROMOTOP MAMMOTH ACCUMULATION EXCHANGER

ROMOTOP MAMMOTH ACCUMULATION SET for ROMOTOP convection exchanger

IMPRESSION R/L 2g L 71.60.34.21 - corner fireplace insert with lifting door and split glazing

IMPRESSION R/L 2g L 83.60.34.21 - corner fireplace insert with lifting door and split glazing

Alternative products

IMPRESSION R/L 2g L 71.60.34.21 - corner fireplace insert with lifting door and split glazing

IMPRESSION R/L 2g L 83.60.34.21 - corner fireplace insert with lifting door and split glazing

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)