



#### **DYNAMIC 2G 66.50.13**

# We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

• DYNAMIC 2G 66.50.13N - straight fireplace insert with triple glazing

DYNAMIC fireplace inserts are well suited for low-energy houses thanks to their double and triple glazing. The glass in the doors includes a design print. Fireplace inserts are equipped with an EAI (external air intake) system and designed for accumulation as well as convection operation. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. A MAMMOTH side accumulation set and upper accumulation rings can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert.

order code: **D2M 13** 

triple glazing

maximum of 2 side accumulation sets

### **Technical parameters**

Height 1003 mm Width 720 mm Depth 397 mm Door height 467 mm Door width 624 mm Weight 175 kg Regulated output 2,4-6,2 kW Smoke flue diameter 150-200 mm Flue socket diameter 200 mm External air intake diameter 150 mm Draught 12 Pa Efficiency 84,6 % Average wood consumption 1,3 kg/h

A+

#### **Accessories**

ACCUMULATION SET of ROMOTOP MAMMOTH RINGS - 6 pcs (AKKUM KV 01B)

ADJUSTABLE LEGS - 190 mm

HANDLING SET

MAMMOTH accumulation ring

PIPE ADAPTOR 200/180 mm

REMOVABLE HANDLE

ROMOTOP CONVECTION EXCHANGER

ROMOTOP MAMMOTH ACCUMULATION EXCHANGER

ROMOTOP MAMMOTH ACCUMULATION SET for ROMOTOP convection exchanger

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

DYNAMIC 2G 66.50.13N - straight fireplace insert with triple glazing

## **Alternative products**

DYNAMIC 2G 66.50.13N - straight fireplace insert with triple glazing

#### **Download**

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet
Warranty sheet
Download our catalogue!