



HEAT 3g L 88.66.01

We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

- HEAT 3G L 88.66.04 - hot-air fireplace insert with lifting door

HEAT fireplace inserts have large-format printed glazing that allows you to experience the fire in a unique way. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The combustion chamber is lined with chamotte bricks and is designed with no furnace grate. However the insert can be fitted with a grate at the customer's request. HEAT fireplace inserts are intended for convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. An EAI (external air intake) system is included. Tertiary air is brought into the combustion chamber to maximize combustion efficiency. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

order code: **H3LJ 01**

maximum of 2 side accumulation sets

Technical parameters

A+

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

CONVECTION COVER (H2LJ KON01)

FRAME H3LF RAM15 support

FRAME H3LJ RAM11 cover standard

FRAME H3LJ RAM12 cover standard

FRAME H3LJ RAM13 standard

FRAME H3LJ RAM14 standard

GRATE SET (H3 ROST 01)

HANDLING SET

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

HEAT 3G L 88.66.04 - hot-air fireplace insert with lifting door

Alternative products

HEAT 3G L 88.66.04 - hot-air fireplace insert with lifting door

Download

Download our catalogue!