



HEAT C 3g L 80.52.31.01(21)

We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

- HEAT C 3G L 80.52.31.24 - hot-air three-sided fireplace insert with lifting door and split glazing

HEAT fireplace inserts have large-format printed three-sided glazing that allows you to experience the fire in a unique way. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The combustion chamber is lined with chamotte bricks and is designed with no furnace grate. However the insert can be fitted with a grate at the customer's request. HEAT fireplace inserts are intended for convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. An EAI (external air intake) system is included. Tertiary air is brought into the combustion chamber to maximise combustion efficiency. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

Bent glazing - order code: **HC3LJ 01**

Split glazing - order code: **HC3LJ 21**

DOUBLE SPIN system

maximum of 1 side accumulation set

HEAT C 3g L 80.52.31.21 K1 is version that includes supporting construction (K1 mark). Order code: **HC3LJ 21 K1**. **Supporting construction cannot be ordered separately!**

Technical parameters

A

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

CONVECTION COVER (HC2LJ KON01)

FRAME HC3LJ RAM11 cover standard

FRAME HC3LJ RAM12 cover standard

FRAME HC3LJ RAM13 standard

FRAME HC3LJ RAM14 standard

FRAME HC3LJ RAM15 support

GRATE SET (H3 ROST 01)

HANDLING SET

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

HEAT C 3G L 80.52.31.24 - hot-air three-sided fireplace insert with lifting door and split glazing

Alternative products

HEAT C 3G L 80.52.31.24 - hot-air three-sided fireplace insert with lifting door and split glazing

Download

Download our catalogue!