



HEAT R/L 2g S 50.51.40.01(21)

We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

• HEAT R/L 2g S 60.44.33.13(23) - corner fireplace insert with bent (split) glazing

HEAT fireplace inserts are intended for convection as well as accumulation operation with the use of ventilation grates. Corner glazing (left, right) is made of two parts. The door frame is made of a special rigid rolled profile. The glass in the doors includes a design print. An EAI (external air intake) system is included. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. A MAMMOTH side accumulation set and upper accumulation rings can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert.

Bent glazing - right variant - order code: HR2SE 01

Bent glazing - left variant - order code: **HL2SE 01**

Split glazing - right variant - order code: HR2SE 21

Split glazing - left variant - order code: HL2SE 21

suitable for low-energy houses

maximum of 2 side accumulation sets

Technical parameters

Height 1126 mm Width 570 mm 470 mm Depth Door height 470 mm Door width 500 mm Door depth 400 mm Weight 130 kg Regulated output 3,3-8,4 kW Smoke flue diameter 150-180 mm Flue socket diameter 180 mm External air intake diameter 125 mm 12 Pa Draught Efficiency 82,0 % 1,9 kg/h Average wood consumption

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 01

A+

GRATE SET (H3 ROST 01)

REMOVABLE HANDLE

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 180 mm

HEAT R/L 2g S 60.44.33.13(23) - corner fireplace insert with bent (split) glazing

Alternative products

HEAT R/L 2g S 60.44.33.13(23) - corner fireplace insert with bent (split) glazing

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!