



## HEAT R/L 2g S 70.44.33.13(23)

**We are sorry, but this model has been sold out and cancelled from our product range.**

HEAT fireplace inserts are intended for convection as well as accumulation operation with the use of ventilation grates. Corner glazing (left, right) is made of two parts. The door frame is made of a special rigid rolled profile. The glass in the doors includes a design print. An EAI (external air intake) system is included. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. A MAMMOTH side accumulation set and upper accumulation rings can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert.

Bent glazing - right variant - order code: **HR2SX 13**

Bent glazing - left variant - order code: **HL2SX 13**

Split glazing - right variant - order code: **HR2SX 23**

Split glazing - left variant - order code: **HL2SX 23**

suitable for low-energy houses

maximum of 2 side accumulation sets

## Technical parameters

A+

## Accessories

ADJUSTABLE LEGS - 100 mm

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

FRAME HR2SX RAM04 4S universal, medium

FRAME HR2SX RAM06 4S universal, shallow

REMOVABLE HANDLE

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 150 mm

## Download

Download our catalogue!