



HEAT R/L 3g L 50.51.40.21

We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

- HEAT R/L 3G L 65.51.40.24 - hot-air corner fireplace insert with lifting door and split glazing
- HEAT R/L 3G L 81.51.40.24 - hot-air corner fireplace insert with lifting door and split glazing

HEAT fireplace inserts have large-format printed corner glazing that allows you to experience the fire in a unique way. Corner glazing (left, right) is made of two parts. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The combustion chamber is lined with chamotte bricks and is designed with no furnace grate. However the insert can be fitted with a grate at the customer's request. HEAT fireplace inserts are intended for convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. An EAI (external air intake) system is included. Tertiary air is brought into the combustion chamber to maximise combustion efficiency. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

Split glazing - right variant - order code: **HR3LE 21**

Split glazing - left variant - order code: **HL3LE 21**

maximum of 2 side accumulation sets

Technical parameters

Height	1357 mm
Width	727 mm
Depth	627 mm
Door height	470 mm
Door width	502 mm
Door depth	397 mm
Weight	197 kg
Regulated output	3,3-8,4 kW
Smoke flue diameter	150-180 mm
Flue socket diameter	180 mm
External air intake diameter	125 mm
Draught	12 Pa
Efficiency	82,0 %
Average wood consumption	1,9 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 01

GRATE SET (H3 ROST 01)

HANDLING SET

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 180 mm

HEAT R/L 3G L 65.51.40.24 - hot-air corner fireplace insert with lifting door and split glazing

HEAT R/L 3G L 81.51.40.24 - hot-air corner fireplace insert with lifting door and split glazing

Alternative products

HEAT R/L 3G L 65.51.40.24 - hot-air corner fireplace insert with lifting door and split glazing

HEAT R/L 3G L 81.51.40.24 - hot-air corner fireplace insert with lifting door and split glazing

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

Warranty sheet

Download our catalogue!