



HEAT R/L 3g L 81.51.40.01(21)

We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

 HEAT R/L 3G L 81.51.40.24 - hot-air corner fireplace insert with lifting door and split glazing

HEAT fireplace inserts have large-format printed corner glazing that allows you to experience the fire in a unique way. Corner glazing (left, right) is made of two parts. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The combustion chamber is lined with chamotte bricks and is designed with no furnace grate. However the insert can be fitted with a grate at the customer's request. HEAT fireplace inserts are intended for convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. An EAI (external air intake) system is included. Tertiary air is brought into the combustion chamber to maximise combustion efficiency. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

Bent glazing - right variant - order code: HR3LF 01

Bent glazing - left variant - order code: HL3LF 01

Split glazing - right variant - order code: HR3LF 21

Split glazing - left variant - order code: **HL3LF 21**

maximum of 2 side accumulation sets

Technical parameters

Height 1357 mm Width 1036 mm 626 mm Depth Door height 470 mm Door width 810 mm Door depth 400 mm Weight 258 kg Regulated output 6,0-15,6 kW Smoke flue diameter 200 mm Flue socket diameter 200 mm External air intake diameter 150 mm Draught 12 Pa 83,2 % Efficiency Average wood consumption 3,4 kg/h

Α+

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

CONVECTION COVER (HL2LF KON01)

CONVECTION COVER (HR2LF KON 01)

FRAME HL3LF RAM11 cover standard

FRAME HL3LF RAM12 cover standard

FRAME HL3LF RAM15 support

FRAME HR3LF RAM11 cover standard

FRAME HR3LF RAM12 cover standard

FRAME HR3LF RAM13 standard, universal

FRAME HR3LF RAM14 standard, universal

FRAME HR3LF RAM15 support

GRATE SET (H3 ROST 01)

HANDLING SET

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

HEAT R/L 3G L 81.51.40.24 - hot-air corner fireplace insert with lifting door and split glazing

Alternative products

HEAT R/L 3G L 81.51.40.24 - hot-air corner fireplace insert with lifting door and split glazing

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!