



HEAT U 3g L 50.52.50.21

We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

 HEAT U 3G L 50.52.50.24 - hot-air three-sided fireplace insert with lifting door and split glasses

HEAT fireplace inserts have large-format printed three-sided glazing that allows you to experience the fire in a unique way. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The combustion chamber is lined with chamotte bricks and is designed with no furnace grate. However the insert can be fitted with a grate at the customer's request. HEAT fireplace inserts are intended for convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. An EAI (external air intake) system is included. Tertiary air is brought into the combustion chamber to maximise combustion efficiency. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

Split glazing - order code: HU3LG 21

without DOUBLE SPIN system

HEAT U 3g L 50.52.50.21 K1 is version that includes supporting construction (K1 mark). Order code: **HU3LG 21 K1**. Supporting construction cannot be ordered separately!

Technical parameters

Height 1382 mm Width 582 mm Depth 749 mm 468 mm Door height Door width 502 mm Door depth 496 mm Weight 234 kg Regulated output 4,0-10,4 kW Smoke flue diameter 200 mm Flue socket diameter 200 mm External air intake diameter 150 mm Axis height of rear outlet 1167 mm Draught 12 Pa Efficiency 83,3 % Average wood consumption 2,3 kg/h

A+

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

CONVECTION COVER (HU3LG KON01)

FRAME HU3LG RAM11 cover standard

FRAME HU3LG RAM12 cover standard

FRAME HU3LG RAM13 standard

FRAME HU3LG RAM14 standard

GRATE SET (H3 ROST 01)

HANDLING SET

HEAT U 3G L 50.52.50.24 - hot-air three-sided fireplace insert with lifting door and split glasses

Alternative products

HEAT U 3G L 50.52.50.24 - hot-air three-sided fireplace insert with lifting door and split glasses

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation
Technical sheet
Warranty sheet

Download our catalogue!