



KV 025 N01

We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

- DYNAMIC 2G 44.55.01N - straight fireplace insert with double glazing
- DYNAMIC 2G 66.50.01N - straight fireplace insert with double glazing

DYNAMIC fireplace inserts are well suited for low-energy houses thanks to their double and triple glazing. The glass in the doors includes a design print. Fireplace inserts are equipped with an EAI (external air intake) system and designed for accumulation as well as convection operation. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. A MAMMOTH side accumulation set and upper accumulation rings can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert.

order code: **KV 025N 01**

intended for permanent accumulation operation with draft systems

double glazing

Technical parameters

Height	990 mm
Width	504 mm
Depth	691 mm
Door height	414 mm
Door width	403 mm
Weight	175 kg
Regulated output	5,3-30,0 kW
Smoke flue diameter	180-200 mm
Flue socket diameter	200 mm
External air intake diameter	150 mm
Draught	12 Pa
Efficiency	90,0 %
Average wood consumption	2,7 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 190 mm

CAST IRON TURNING DOME 180

CAST IRON TURNING DOME 200

MAMMOTH accumulation ring

PIPE ADAPTOR 200/180 mm

ROMOTOP CONVECTION EXCHANGER

ROMOTOP MAMMOTH ACCUMULATION EXCHANGER

ROMOTOP MAMMOTH ACCUMULATION SET for ROMOTOP convection exchanger

DYNAMIC 2G 44.55.01N - straight fireplace insert with double glazing

DYNAMIC 2G 66.50.01N - straight fireplace insert with double glazing

Alternative products

DYNAMIC 2G 44.55.01N - straight fireplace insert with double glazing

DYNAMIC 2G 66.50.01N - straight fireplace insert with double glazing

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!