Romotop®



KV 025 W02 BD

We are sorry, but this model has been sold out and cancelled from our product range.

Please look at following alternative models:

- DYNAMIC WB 2g 66.50.01P - fireplace insert with back stoking, triple glazing and hot-water exchanger

Variability of design in combination with the truly great structural properties of the DYNAMIC range of fireplace inserts guarantees warm, carefree times even in the harshest winter. Let Romotop DYNAMIC fireplace inserts do the work for you.

order code: **KV 025W 02BD**

Technical parameters

Height	1272 mm
Width	826 mm
Depth	595 mm
Door height	467 mm
Door width	624 mm
Weight	307 kg
Regulated output	6,0-15,6 kW
Regulated output of water exchanger	4,1-10,7 kW
Smoke flue diameter	180 mm
Flue socket diameter	180 mm
External air intake diameter	150 mm
Draught	12 Pa
Efficiency	89,5 %
Average wood consumption	3,0 kg/h

A+

Accessories

ADJUSTABLE LEGS - 190 mm
HANDLING SET
TECHNICAL FRAME (KV 025WBRAM01)
DYNAMIC WB 2g 66.50.01P - fireplace insert with back stoking, triple glazing and hot-water exchanger

Alternative products

DYNAMIC WB 2g 66.50.01P - fireplace insert with back stoking, triple glazing and hot-water exchanger

Download

Construction readiness - heating sets
Declaration about qualities
EC declaration of conformity
Ecodesign (EU 2015/1185)
Energy label and product sheet
Energy label (EU 2015/1186)
General instructions
Installation instructions
Technical documentation
Technical sheet
Warranty sheet
Download our catalogue!