



## **LUGO N 04 BF**

**We are sorry, but this model has been sold out and cancelled from our product range.**

Please look at following alternative models:

- LUGO N 01 BF ceramic - fireplace stove with oven
- LUGO N 02 BF serpentine - fireplace stove with oven
- LUGO N 03 BF steel - fireplace stove with oven

This fireplace stove is suitable for low-energy homes. The stainless oven with a high quality thermometer will always produce a perfect meal. The door can be locked in the open position. The ventilated designer handle permits use when the stove is lit. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for storing a small amount of wood or tools.

order code: **LUGO N 04 BF**

## Technical parameters

Height	1552 mm
Width	550 mm
Depth	456 mm
Weight	193 kg
Regulated output	3,0-7,8 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1369 mm
Draught	12 Pa
Efficiency	81,9 %
Average wood consumption	1,7 kg/h
A+	

## Alternative products

LUGO N 01 BF ceramic - fireplace stove with oven  
LUGO N 02 BF serpentine - fireplace stove with oven  
LUGO N 03 BF steel - fireplace stove with oven

## Download

Declaration about qualities  
EC declaration of conformity  
Ecodesign (EU 2015/1185)  
Energy label and product sheet  
Energy label (EU 2015/1186)  
General instructions  
Installation instructions  
Technical documentation  
Technical sheet  
Warranty sheet  
Download our catalogue!