



## **TALA 06**

**We are sorry, but this model has been sold out and cancelled from our product range.**

Please look at following alternative models:

- TALA N 06 steel - fireplace stove

This fireplace stove is suitable for all types of interiors. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood.

order code: **TALA 06**

## Technical parameters

Height	1064 mm
Width	500 mm
Depth	390 mm
Weight	110 kg
Regulated output	3,0-7,7 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
Axis height of rear outlet	960 mm
Draught	12 Pa
Efficiency	80,1 %
Average wood consumption	1,7 kg/h
A	

## Alternative products

TALA N 06 steel - fireplace stove

## Download

[Declaration about qualities](#)  
[EC declaration of conformity](#)  
[Ecodesign \(EU 2015/1185\)](#)  
[Energy label and product sheet](#)  
[Energy label \(EU 2015/1186\)](#)  
[General instructions](#)  
[Installation instructions](#)  
[Technical documentation](#)  
[Technical sheet](#)  
[Warranty sheet](#)  
[Download our catalogue!](#)