

## **DYNAMIC fireplace inserts** FOR LONG-LASTING ACCUMULATION HEATING WITH DOUBLE GLAZING

**DYNAMIC fireplace inserts are the ideal choice for installations using accumulation elements. When assembled, these radiant accumulation stoves are the result of cooperation between the stove builder and the user. The output, size of the combustion chamber and the amount of accumulation are scaled to the specific building and the customer's requirements. Thanks to the ability to store and radiate heat, accumulation stoves are among the best and healthiest means of heating. Fire-place inserts should be purchased with MAMMOTH accumulation rings or the accumulation modular system, which represents the ultimate in heat storage.**

DYNAMIC fireplace inserts have a design print on the double glazed door (suitable for low-energy houses when installed with accumulation casing). They have an external air intake (EAI) system, and are designed for closed, built-in accumulation. The combustion chamber is lined with 5 cm thick chamotte bricks and thanks to the secondary air intake, the glass on the door is constantly "washed" to prevent the build-up of deposits. The primary and secondary (tertiary) air intake can be regulated by a single control element. DYNAMIC fireplace inserts are not supplied with smoke extraction components (spigot). The customer must buy these separately as accessories according to the intended use. **The fireplace insert cannot be connected directly to the chimney.**

### **DYNAMIC R/L 3G S 55.44.42.21**



Prices on request at your seller

Split glazing - right variant - order code: **DR3SG 21**

Split glazing - left variant - order code: **DL3SG 21**



## Technical parameters

Height	894 mm
Width	698 mm
Depth	605 mm
Door height	394 mm
Door width	554 mm
Door depth	424 mm
Weight	183 kg
Regulated output	5,0-13,0 kW
Smoke flue diameter	180 / 200 mm
Flue socket diameter	180 / 200 mm
External air intake diameter	150 mm
Draught	10 Pa
Efficiency	82,7 %
Average wood consumption	2,8 kg/h
A+	

## Accessories

ACCUMULATION SET of ROMOTOP MAMMOTH RINGS - 8 pcs (AKKUM KV 08B)

ADJUSTABLE LEGS - 190 mm

AIRBOX 01 IMPRESSION

CAST IRON FLANGE 200

CAST IRON TURNING DOME WITH ELBOW 180

FRAME DR3SG RAM04 cover deep universal

FRAME DR3SG RAM06 cover standard universal

HOT AIR EXCHANGER for DYNAMIC 3G fireplace inserts

MAMMOTH accumulation ring

RECESSED HANDLE

REMOVABLE HANDLE

## Download

[Declaration about qualities](#)

[Energy label and product sheet](#)

[Instruction manual](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)