

DYNAMIC fireplace inserts WITH DOUBLE / TRIPLE GLAZING AND BACK STOKING

DYNAMIC fireplace inserts with double and triple glazing and back stoking meet all the requirements of modern buildings. You can stoke from a different room and thus achieve maximum user comfort.

DYNAMIC fireplace inserts are well suited for low-energy houses thanks to their double and triple glazing. The back stoking door allows you to comfortably add wood to the combustion chamber. The glass in the doors includes a design print. Right-sided opening doors can be switched to left-sided opening. Fireplace inserts are equipped with an EAI (external air intake) system and designed for accumulation as well as convection operation. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. Secondary air intake washes over the glass in the door to prevent the accumulation of deposits. Primary and secondary air intake is regulated by a single control element. A MAMMOTH side accumulation set and upper accumulation rings can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert.

DYNAMIC B2G 35.46.01

steel



Prices on request at your seller

order code: **DB2K 01**

double glazing

maximum of 2 side accumulation sets

without DOUBLE SPIN system



Technical parameters

Height	990 mm
Width	514 mm
Depth	492 mm
Door height	426 mm
Door width	305 mm
Weight	145 kg
Regulated output	2,0-6,0 kW
Smoke flue diameter	150-200 mm
Flue socket diameter	200 mm
External air intake diameter	125 mm
Draught	12 Pa
Efficiency	80,3 %
Average wood consumption	1,1 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 190 mm

FRAME D2K RAM03 3S medium

FRAME D2K RAM04 4S medium

FRAME D2K RAM06 4S

MAMMOTH accumulation ring

PIPE ADAPTOR 200/180 mm

REMOVABLE HANDLE

ROMOTOP CONVECTION EXCHANGER

ROMOTOP MAMMOTH ACCUMULATION EXCHANGER

ROMOTOP MAMMOTH ACCUMULATION SET for ROMOTOP convection exchanger

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TECHNICAL FRAME DB2K RAM01 4S

Download

Declaration about qualities

Energy label and product sheet

General instructions

Technical documentation

Technical sheet

Warranty certificate

Download our catalogue!