

HEAT fireplace inserts WITH HOT-WATER EXCHANGER

HEAT fireplace inserts with a hot-water exchanger are a hot trend in central heating. The powerful and efficient hot-water exchanger will find applications in various types of buildings and offers long-lasting pleasant warmth.

HEAT fireplace inserts with a hot-water exchanger come with TRIPLE PASS, a special patented design hot-water exchanger that will increase fireplace insert efficiency by up to 10%. The door frame is made of a special rigid rolled profile. Fireplace inserts are equipped with an EAI (external air intake) system and designed for convection operation. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. Secondary air intake washes over the glass in the door to prevent the accumulation of deposits. Primary and secondary air intake is regulated by a single control element. Safety is ensured by an integrated cooling loop and the package also includes air-escape valve. A cleaning opening to easily clean the hot-water exchanger further adds to user comfort.

HEAT W 2g 70.50.01

steel



Prices on request at your seller

order code: **HW2Z 01**

exchanger volume of 61 l



Technical parameters

Height	1208 mm
Width	800 mm
Depth	502 mm
Door height	467 mm
Door width	664 mm
Weight	245 kg
Regulated output	7,3-18,9 kW
Regulated output of water exchanger	5,2-13,4 kW
Smoke flue diameter	180 mm
Flue socket diameter	180 mm
External air intake diameter	150 mm
Draught	11 Pa
Efficiency	89,1 %
Average wood consumption	4,0 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 100 mm

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

CONVECTION COVER WITH INSULATION

FRAME H2Z RAM04 cover deep 4S

FRAME H2Z RAM06 4S

REMOVABLE HANDLE

Download

Construction readiness

Construction readiness - heating sets

Declaration about qualities

Energy label and product sheet

Instruction manual

Technical documentation

Technical sheet

Warranty certificate

Download our catalogue!