

## HEAT fireplace inserts WITH LIFTING DOOR AND BENT / SPLIT CORNER GLAZING

Above-standard large corner glazing makes HEAT fireplace inserts with lifting doors a dominant feature of every room. Clean lines together with the precise curvature of the glass perfectly reflects the requirements of contemporary design.

HEAT fireplace inserts have large-format printed corner glazing that allows you to experience the fire in a unique way. Corner glazing (left, right) can be curved or made of two parts. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The combustion chamber is lined with chamotte bricks and is designed with no furnace grate. However the insert can be fitted with a grate at the customer's request. HEAT fireplace inserts are intended for convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. An EAI (external air intake) system is included. Tertiary air is brought into the combustion chamber to maximise combustion efficiency. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

### HEAT R/L 3g L 81.51.40.01(21)



Prices on request at your seller

Not available anymore - Bent glazing - right variant - order code: **HR3LF 01**

Not available anymore - Bent glazing - left variant - order code: **HL3LF 01**

Split glazing - right variant - order code: **HR3LF 21**

Split glazing - left variant - order code: **HL3LF 21**

maximum of 2 side accumulation sets



## Technical parameters

Height	1357 mm
Width	1036 mm
Depth	626 mm
Door height	470 mm
Door width	810 mm
Door depth	400 mm
Weight	258 kg
Regulated output	6,0-15,6 kW
Smoke flue diameter	200 mm
Flue socket diameter	200 mm
External air intake diameter	150 mm
Draught	12 Pa
Efficiency	83,2 %
Average wood consumption	3,4 kg/h
A+	

## Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

CONVECTION COVER for HEAT L 3g L 81.51.40.01(21) fireplace insert

CONVECTION COVER for HEAT R 3g L 81.51.40.01(21) fireplace insert

FRAME HL3LF RAM11 cover standard

FRAME HL3LF RAM12 cover standard

FRAME HL3LF RAM15 support

FRAME HR3LF RAM11 cover standard

FRAME HR3LF RAM12 cover standard

FRAME HR3LF RAM13 standard, universal

FRAME HR3LF RAM14 standard, universal

FRAME HR3LF RAM15 support

GRATE SET (H3 ROST 01)

HANDLING SET

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

## **Download**

Declaration about qualities

Energy label and product sheet

Instruction manual

Technical documentation

Technical sheet

Warranty certificate

Download our catalogue!