

Technical parameters

Height	1357 mm
Width	876 mm
Depth	626 mm
Door height	470 mm
Door width	650 mm
Door depth	400 mm
Weight	247 kg
Regulated output	3,5-9,0 kW
Smoke flue diameter	180-250 mm
Flue socket diameter	200 mm
External air intake diameter	150 mm
Draught	12 Pa
Efficiency	84,8 %
Average wood consumption	1,9 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

CONVECTION COVER (HL2LG KON 01)

CONVECTION COVER (HR2LG KON 01)

FRAME HL3LG RAM11 cover standard

FRAME HL3LG RAM12 cover standard

FRAME HL3LG RAM15 support

FRAME HR3LG RAM11 cover standard

FRAME HR3LG RAM12 cover standard

FRAME HR3LG RAM13 standard, universal

FRAME HR3LG RAM14 standard, universal

FRAME HR3LG RAM15 support

GRATE SET (H3 ROST 04)

HANDLING SET

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)