

HEAT fireplace inserts WITH LIFTING DOOR AND SPLIT CORNER GLAZING

The large glazing of HEAT fireplace inserts provides a pleasant view of the fire from all corners of your room. The lifting door is a convenient feature and belongs to the modern design of this series.

Corner glazing (left, right) is made of two parts. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The combustion chamber is lined with heat-resistant bricks named IGNITON and is designed with no furnace grate. However the insert can be fitted with a grate at the customer's request. HEAT fireplace inserts are intended for convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. An EAI (external air intake) system is included. Tertiary air is brought into the combustion chamber to maximise combustion efficiency. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

HEAT R/L 3G L 81.51.40.24



Prices on request at your seller

Split glazing - right variant - order code: **HR3LF 24**

Split glazing - left variant - order code: **HL3LF 24**

maximum of 2 side accumulation sets

ecodesign
READY



Technical parameters

Height	1357 mm
Width	1036 mm
Depth	626 mm
Door height	470 mm
Door width	810 mm
Door depth	400 mm
Weight	258 kg
Regulated output	6,0-15,6 kW
Smoke flue diameter	200 mm
Flue socket diameter	200 mm
External air intake diameter	150 mm
Draught	12 Pa
Efficiency	83,2 %
Average wood consumption	3,4 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

CONVECTION COVER (HL2LF KON01)

CONVECTION COVER (HR2LF KON 01)

FRAME HL3LF RAM11 cover standard

FRAME HL3LF RAM12 cover standard

FRAME HL3LF RAM15 support

FRAME HR3LF RAM11 cover standard

FRAME HR3LF RAM12 cover standard

FRAME HR3LF RAM13 standard, universal

FRAME HR3LF RAM14 standard, universal

FRAME HR3LF RAM15 support

GRATE SET (H3 ROST 04)

HANDLING SET

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)