

## IMPRESSION fireplace inserts WITH LIFTING DOOR AND SPLIT CORNER GLAZING

Carefully balanced proportions, clean lines and dominant large corner glazing make the IMPRESSION corner fireplace insert with lifting door the perfect choice. The timeless design makes it the perfect fit for modern interiors.

IMPRESSION fireplace inserts have unusually high glass windows, offering a luxurious view of the fire. Corner glazing (left, right) consists of two parts. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The lifting door is operated using a removable handle, which can optionally be replaced by a fixed handle. The combustion chamber is available in black or cream colour with an optional change for the furnace grate. Inserts are designed for both accumulation and convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. Fireplace inserts are equipped with an EAI (external air intake) system, which can be easily connected using the AIRBOX rotating elbow. The flue gas exhaust can be connected from the side or the top. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

### IMPRESSION R/L 2g L 71.60.34.21



Prices on request at your seller

Split glazing - right variant - order code: **IR2LG 21**

Split glazing - left variant - order code: **IL2LG 21**

maximum of 3 side accumulation sets

the combustion chamber is optional (crema or black) and needs be ordered separately!



## Technical parameters

[LT: Výška]	1531 [LT: mm]
[LT: Šířka]	943 [LT: mm]
[LT: Hloubka]	574 [LT: mm]
[LT: Výška dvířek]	556 [LT: mm]
[LT: Šířka dvířek]	706 [LT: mm]
[LT: Hloubka dvířek]	339 [LT: mm]
[LT: Hmotnost]*	221 [LT: kg]
[LT: Regulovatelný výkon]	5,0-13,0 [LT: kW]
[LT: Průměr kouřovodu]	150-200 [LT: mm]
[LT: Průměr kouřového hrdla]	200 [LT: mm]
[LT: Průměr centr. přív. vzduchu (CPV)]	150 [LT: mm]
[LT: Výška osy zadního vývodu]	1190 [LT: mm]
[LT: Provozní tah]	12 [LT: Pa]
[LT: Účinnost]	81,0 %
[LT: Průměrná spotřeba dřeva]	2,8 [LT: kg/h]

\*weight including black / cream combustion chamber

A+

## Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 01 IMPRESSION

COMBUSTION CHAMBER IR2LG TOP01 black

COMBUSTION CHAMBER IR2LG TOP02 cream

CONTRA-WEIGHT IMPRESSION

CONVECTION COVER for IMPRESSION R/L 2g L 71.60.34.21 fireplace inserts

FRAME IL2LG RAM11 cover standard

FRAME IL2LG RAM12 cover standard

FRAME IL2LG RAM15 support

FRAME IR2LG RAM11 cover standard

FRAME IR2LG RAM12 cover standard

FRAME IR2LG RAM13 standard, universal

FRAME IR2LG RAM14 standard, universal

FRAME IR2LG RAM15 support

GRATE SET (H3 ROST 01)

HANDLING SET

IMPRESSION FIXED HANDLE

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts (AKKUM KV 06)

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

## Download

[LT: Energetický štítek a informační list výrobku]

[LT: Návod k obsluze]

[LT: Prohlášení o vlastnostech]

[LT: Technická dokumentace]

[LT: Technický list]

Warranty certificate

Download our catalogue!