

The LUGO N fireplace stove will give your household a personal style. Its unique design combined with state-of-the-art combustion technology will lend your home a pleasant atmosphere.

LUGO N Fireplace stoves

The oval shape of the LUGO N fireplace stove helps create a cosy interior. It includes pleasant details, such as a sill above the combustion chamber or the door handle whose technical design lends the fireplace stove an elegant look.

This fireplace stove is suitable for low-energy homes. An EAI (External Air Intake) system is included. The ventilated designer handle permits use when the stove is lit. The door can be locked in the open position. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for storing a small amount of wood or tools.

LUGO N 04

sandstone



Prices on request at your seller

order code: **LUGO N 04**



Technical parameters

| | |
|------------------------------|------------|
| Height | 1224 mm |
| Width | 550 mm |
| Depth | 438 mm |
| Weight | 180 kg |
| Regulated output | 3,0-7,8 kW |
| Smoke flue diameter | 150 mm |
| Flue socket diameter | 150 mm |
| External air intake diameter | 125 mm |
| Axis height of rear outlet | 922 mm |
| Draught | 12 Pa |
| Efficiency | 81,9 % |
| Average wood consumption | 1,7 kg/h |
| A+ | |

Download

[Declaration about qualities](#)

[Energy label and product sheet](#)

[Instruction manual](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)