

The ALEA fireplace stove includes a rotating design that allows you to enjoy viewing the flames from multiple angles.

ALEA Fireplace stoves

The elegant, slim shape of the ALEA fireplace stove is a perfect match for every interior. The rotating combustion chamber means you won't be restricted to watching the beautiful living flames from just a single angle.

This fireplace stove is suitable for low-energy homes. An EAI (External Air Intake) system is included. The ventilated designer handle permits use when the stove is lit. The door can be locked in the open position. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The rotating combustion chamber allows you to view your fire from multiple angles.

ALEA 03

steel



Prices on request at your seller
order code: **ALEA 03**



Technical parameters

Height	1243 mm
Width	468 mm
Depth	468 mm
Weight	149 kg
Regulated output	2,9-7,4 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1129.5 mm
Draught	11 Pa
Efficiency	82,9 %
Average wood consumption	1,6 kg/h
A+	

Download

- Declaration about qualities
- Energy label and product sheet
- General instructions
- Technical documentation
- Technical sheet
- Warranty certificate
- Download our catalogue!