

Experience the beauty of dancing flames right in your home. With its three-sided glazing, the BELO 3S fireplace stove offers an above-standard view of your fire.

## BELO 3S Fireplace stoves

**Minimalistic construction and clean design make the BELO 3S suitable for any interior. The panoramic fully glazed door and side glazing give you a view of the fire from multiple angles.**

This fireplace stove is suitable for low-energy homes. The fully glazed door is decorated with designer prints. The triple-sided glazing allows you to view the fire from multiple angles. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for a small amount of wood or tools.

### BELO 3S 03

steel



order code: **BELO 3S 03**



## Technical parameters

Height	1189 mm
Width	533 mm
Depth	406 mm
Door height	880 mm
Door width	447 mm
Door depth	129 mm
Weight	152 kg
Regulated output	2,5-6,4 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1073 mm
Draught	12 Pa
Efficiency	80,5 %
Average wood consumption	1,4 kg/h
A+	

## Download

[Declaration about qualities](#)  
[Energy label and product sheet](#)  
[General instructions](#)  
[Technical documentation](#)  
[Technical sheet](#)  
[Warranty certificate](#)  
[Download our catalogue!](#)