

BURGOS Fireplace stoves

A generous combustion chamber with high quality design components and precise, clean lines. The BURGOS fireplace stove gives any interior a unique atmosphere.

This fireplace stove is the perfect fit for modern interiors in particular. The ventilated designer handle permits use when the stove is lit. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood.

BURGOS 02

serpentine



Prices on request at your seller
order code: **BRGS 02**



Technical parameters

Height	1176 mm
Width	756 mm
Depth	507 mm
Weight	243 kg
Regulated output	3,8-9,8 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1008 mm
Draught	11 Pa
Efficiency	82,7 %
Average wood consumption	2,1 kg/h
A+	

Download

[Declaration about qualities](#)
[Energy label and product sheet](#)
[General instructions](#)
[Technical documentation](#)
[Technical sheet](#)
[Warranty certificate](#)
[Download our catalogue!](#)