

ESQUINA 3G Fireplace stoves

The compact square-shaped fireplace stove model with its high corner glass door catches the eye with its unique view of the fire from all angles.

The ESQUINA 3G fireplace stove is suitable for low-energy homes. An EAI (External Air Intake) system is included. The ventilated designer handle permits use when the stove is lit. The door can be locked in the open position. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with white MATRIX chamotte brick. The primary and secondary air intakes are regulated by a single control element.

ESQUINA 3G

steel



Prices on request at your seller

order code: **ESQUINA 3G**



Technical parameters

Height	1506 mm
Width	403 mm
Depth	403 mm
Weight	170 kg
Regulated output	3,0-7,7 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1383 mm
Draught	12 Pa
Efficiency	81,4 %
Average wood consumption	1,7 kg/h
A+	

Accessories

[BOX low narrow](#)

[BOX low wide](#)

[BOX tall](#)

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[Instruction manual](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)