

The shape and design of the EVORA fireplace stoves closely follow the latest interior design trends. EVORA is a great choice for a wide spectrum of customers and has become a highly popular model.

## EVORA T Fireplace stoves

**The EVORA T fireplace stoves provides more than one point of view of the flames. The rotating combustion chamber allows you to view your fire from multiple angles.**

This fireplace stove is suitable for low-energy homes. An EAI (External Air Intake) system is included. The standard version includes an upper flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element.

### EVORA T 01

ceramic



Prices on request at your seller

order code: **EVORA T 01**



## Glaze colours



## Technical parameters

Height	997 mm
Width	528 mm
Depth	398 mm
Weight	124 kg
Regulated output	2,0-6,5 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	863 mm
Draught	12 Pa
Efficiency	80,5 %
Average wood consumption	1,2 kg/h

A

## Download

- [Declaration about qualities](#)
- [EC declaration of conformity](#)
- [Ecodesign \(EU 2015/1185\)](#)
- [Energy label and product sheet](#)
- [Energy label \(EU 2015/1186\)](#)
- [Instruction manual](#)
- [Technical documentation](#)
- [Technical sheet](#)
- [Warranty certificate](#)
- [Download our catalogue!](#)