

## IRUN N Fireplace stoves

**IRUN N fireplace stoves have a narrow oval body that allows their installation in smaller low-energy homes. The stove design is accentuated by a fully glazed door with a modern print and a designer handle for easy opening.**

This fireplace stove is suitable for low-energy homes. Door opening and closing uses a hydraulic system that ensures a perfect seal. The fully glazed door is decorated with designer prints. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for a small amount of wood or tools.

### IRUN N 03

steel



Prices on request at your seller  
order code: **IRUN N 03**



## Technical parameters

Height	1097 mm
Width	458 mm
Depth	458 mm
Weight	136 kg
Regulated output	3,0-7,7 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	998 mm
Draught	12 Pa
Efficiency	81,0 %
Average wood consumption	1,6 kg/h
A+	

## Download

- Declaration about qualities
- Energy label and product sheet
- General instructions
- Technical documentation
- Technical sheet
- Warranty certificate
- Download our catalogue!