

The oval shape of the LUGANO fireplace stove lends your interior a cosy feeling. The design is accentuated by a fully glazed stove door.

LUGANO A Fireplace stoves

The LUGANO A fireplace stove can be fitted with special accumulation tiles in the space above the combustion chamber. This “mass” of accumulation elements can extend the heat radiation period of the stove by several hours.

This fireplace stove is suitable for low-energy homes. The stove door includes a large glazed area with a designer print. The ventilated designer handle permits use when the stove is lit. The door can be locked in the open position. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for a small amount of wood or tools. Additionally, you can purchase extra accumulation elements that radiate heat for up to 5.5 hours.

LUGANO 02 A

serpentine



Prices on request at your seller

order code: **LUGANO 02 A**

Technical parameters

Height	1530 mm
Width	550 mm
Depth	457 mm
Weight	200 kg
Regulated output	3,0-7,8 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	988/1289 mm
Draught	12 Pa
Efficiency	81,9 %
Average wood consumption	1,7 kg/h
A+	

Accessories

Accumulation set for fireplace stoves (AKKUM 01)

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)