

The OVALIS fireplace stove and its large combustion chamber will allow you to enjoy an entertaining view of the flames.

OVALIS Fireplace stoves

The compact shape of the OVALIS fireplace stove combined with the wide combustion chamber make it a perfect fit for your interior.

This fireplace stove is suitable for low-energy homes. The designer stainless steel ventilated handle permits use when the stove is lit. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood.

OVALIS 02

serpentine



Prices on request at your seller
order code: **OVALIS 02**



Technical parameters

| | |
|------------------------------|------------|
| Height | 1071 mm |
| Width | 630 mm |
| Depth | 398 mm |
| Door height | 678 mm |
| Door width | 534 mm |
| Door depth | 114 mm |
| Weight | 156 kg |
| Regulated output | 3,0-7,8 kW |
| Smoke flue diameter | 150 mm |
| Flue socket diameter | 150 mm |
| External air intake diameter | 125 mm |
| Axis height of rear outlet | 938 mm |
| Draught | 11 Pa |
| Efficiency | 83,5 % |
| Average wood consumption | 1,6 kg/h |
| A+ | |

Download

[Declaration about qualities](#)
[Energy label and product sheet](#)
[General instructions](#)
[Technical documentation](#)
[Technical sheet](#)
[Warranty certificate](#)
[Download our catalogue!](#)