

SALEM Fireplace stoves

The SALEM fireplace stove with a large door is for those who love a prominent and clear-cut design. This stove can create magic moments in every house.

This fireplace stove is suitable for low-energy homes. The stove door includes a large glazed area. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the accumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood.

SALEM 03

steel



Prices on request at your seller
order code: **SALEM 03**



Technical parameters

Height	840 mm
Width	750 mm
Depth	319 mm
Door height	588 mm
Door width	644 mm
Weight	141 kg
Regulated output	3,0-7,8 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	729 mm
Draught	11 Pa
Efficiency	83,5 %
Average wood consumption	1,6 kg/h
A+	

Download

[Declaration about qualities](#)
[Energy label and product sheet](#)
[General instructions](#)
[Technical documentation](#)
[Technical sheet](#)
[Warranty certificate](#)
[Download our catalogue!](#)