

## TALA N Fireplace stoves

**The defining feature of the TALA N is the large door for an unobstructed view of the fire. The main material used for the body is sheet metal, which also determines the overall impression of the stove.**

This fireplace stove is suitable for all types of interiors. The design of the stove allows optional flue connection both ways, top or rear. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood.

### TALA N 01

steel



Prices on request at your seller  
order code: **TALA N 01**



## Technical parameters

Height	1064 mm
Width	480 mm
Depth	433 mm
Weight	113 kg
Regulated output	3,0-7,7 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
Axis height of rear outlet	960 mm
Draught	12 Pa
Efficiency	78,0 %
Average wood consumption	1,8 kg/h

A

## Download

[Declaration about qualities](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[Instruction manual](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty certificate](#)

[Download our catalogue!](#)