

TALA Fireplace stoves

The dominant feature of this TALA stove is the large door, allowing you to enjoy watching the flames from anywhere in the room.

This fireplace stove is suitable for all types of interiors. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood.

TALA 06

steel



Prices on request at your seller

order code: **TALA 06**

Technical parameters

| | |
|----------------------------|------------|
| Height | 1064 mm |
| Width | 500 mm |
| Depth | 390 mm |
| Weight | 110 kg |
| Regulated output | 3,0-7,7 kW |
| Smoke flue diameter | 150 mm |
| Axis height of rear outlet | 960 mm |
| Draught | 12 Pa |
| Efficiency | 80,1 % |
| Average wood consumption | 1,7 kg/h |
| A+ | |

Download

- [Declaration about qualities](#)
- [Energy label and product sheet](#)
- [Instruction manual](#)
- [Technical documentation](#)
- [Technical sheet](#)
- [Warranty certificate](#)
- [Download our catalogue!](#)